

Typ	Rotor- x Rotor-Breite	Gewicht einschl. Fundamentrahmen	ca. Leistung	Antriebsleistung
LTH I 490 / 190	490 / 190	750 kg	1,8 t/h	7,5 - 22 KW
LTH I 490 / 380	490 / 380	1.000 kg	3 - 4 t/h	11 - 30 KW
LTH I 650 / 250	650 / 250	1.350 kg	4 t/h	15 - 45 KW
LTH I 650 / 500	650 / 500	1.600 kg	7 t/h	18 - 55 KW
LTH I 650 / 750	650 / 750	2.500 kg	9 - 10 t/h	22 - 75 KW
LTH I 1000 / 750	1000 / 750	5.700 kg	15 - 18 t/h	30 - 160 KW
LTH I 1000 / 1250	1000 / 1250	7.600 kg	22 - 25 t/h	45 - 200 KW
LTH I 1000 / 2000	1000 / 2000	13.600 kg	30 - 35 t/h	55 - 250 KW
LTH I 1300 / 2500	1300 / 2500	25.400 kg	55 - 60 t/h	75 - 300 KW
LTH I 1600 / 2500	1600 / 2500	37.500 kg	70 t/h	90 - 350 KW
LTH I 2000 / 2500	2000 / 2500	50.100 kg	90 t/h	132 - 500 KW
LTH I 2500 / 2500	2500 / 2500	60.200 kg	110 t/h	160 - 750 KW