

rotor-Ø x rotor-width	feed size	power requi- rements	crusher speed	final particle size	infeed HxW	weight in kg (approx.)
400 / 300	200 mm	5,5 kW	4 t/h	0 - 45 mm	320 x 360	1.000
600/450	200 mm	15 kW	15 t/h	0 - 45 mm	390 x 450	2.200
760 / 670	350 mm	60 kW	25 t/h	0 - 45 mm	570 x 690	3.800
800 / 100	400 mm	75 kW	65 t/h	0 - 45 mm	630 x 1020	5.000
800 / 1300	400 mm	90 kW	95 t/h	0 - 45 mm	630 x 1360	6.100
1000 / 700	440 mm	55 kW	50 t/h	0 - 45 mm	760 x 690	5.100
1000 / 1000	440 mm	90 kW	80 t/h	0 - 45 mm	760 x 1020	8.000
1000 / 1300	630 mm	132 kW	120 t/h	0 - 45 mm	900 x 1360	14.500
1000 / 2010	630 mm	200 kW	210 t/h	0 - 45 mm	900 x 2030	16.500
1300 / 1000	710 mm	132 kW	110 t/h	0 - 45 mm	1000 x 1020	16.750
1300 / 1200	700 mm	160 kW	180 t/h	0 - 45 mm	1000 x 1220	20.000
1300 / 1300	710 mm	160 kW	180 t/h	0 - 45 mm	1000 x 1360	20.500
1300 / 2010	710 mm	300 kW	300 t/h	0 - 45 mm	1000 x 2030	22.300
1300 / 1500	800 mm	200 kW	220 t/h	0 - 45 mm	1120 x 1360	22.500
1600 / 1500	830 mm	250 kW	350 t/h	0 - 45 mm	1180 x 1520	45.000
1600 / 1800	830 mm	350 kW	420 t/h	0 - 45 mm	1180 x 1820	52.000