

Rotor-Ø x rotorbreedte	Toevoer stukgr.	Vereiste kracht	Breker-vermogen	Eindkorrel	Inlaat HxB	Gewicht in kg (ca.)
760 / 670 M	300 mm	45 kW	35 t/h	0 - 32 mm	570 x 690	4.300
800 / 1000 M	350 mm	90 kW	80 t/h	0 - 32 mm	630 x 1020	5.700
800 / 500 M	0 mm	0 kW	0 t/h	0 - 32 mm	0 x 0	0
850 / 670 M	0 mm	0 kW	0 t/h	0 - 32 mm	0 x 0	0
1000 / 700 M	300 mm	75 kW	65 t/h	0 - 32 mm	760 x 690	6.200
1000 / 1000 M	360 mm	132 kW	90 t/h	0 - 32 mm	760 x 1020	9.100
1000 / 1300 M	400 mm	160 kW	140 t/h	0 - 32 mm	900 x 1360	15.700
1300 / 1000 M	600 mm	160 kW	160 t/h	0 - 32 mm	1000 x 1020	18.000
1300 / 1300 M	600 mm	240 kW	230 t/h	0 - 32 mm	1000 x 1360	20.500
1300 / 1500 M	600 mm	240 kW	280 t/h	0 - 32 mm	1000 x 1520	23.500